

206-00 Brake System - General Information
Specifications

2024 Mustang

Procedure revision date: 03/15/2023

Specifications

Lubricants, Fluids, Sealers and Adhesives

	Specifications
Motorcraft® DOT 4 LV High Performance Motor Vehicle Brake Fluid / PM-20	WSS-M6C65-A2

Torque Specifications

Item	Nm	lb-ft	lb-in
Front caliper bleeder screw-vehicles with 2 piston brake caliper (Base 2.3L)	8.33	-	73.77
Front caliper bleeder screw-vehicles with 4 piston brake caliper (Base GT)	19	-	168.15
Front caliper bleeder screw-vehicles with 6 piston brake caliper (I4 / GT Performance / Feature Car)	19	-	168.15
Rear caliper bleeder screw (Base 2.3L)	10	-	88.50
Rear caliper bleeder screw (Base GT)	10	-	88.50
Rear caliper bleeder screw (I4 / GT Performance / Feature Car)	19	-	168.15
Master cylinder brake tube fittings	18	-	133

General Specifications

Item	Specification
Front brake disc minimum thickness-vehicles with 2 piston brake caliper (Base 2.3L)	1.122 in (28.5 mm)
Front brake disc minimum thickness-vehicles with 4 piston brake caliper (Base GT)	1.201 in (30.5 mm)
Front brake disc minimum thickness-vehicles with 6 piston brake caliper 1-piece and 2-piece discs (I4 / GT Performance / Feature Car)	1.339 in (34 mm)
Rear brake disc minimum thickness-solid (Base 2.3L)	0.413 in (10.5 mm)
Rear brake disc minimum thickness-vented (Base GT)	0.965 in (24.5 mm)
Rear brake disc minimum thickness-vented (I4 / GT Performance / Feature Car)	1.043 in (26.5 mm)
Brake pad minimum thickness	0.118 in (3 mm)
Brake pad maximum taper wear (in any direction)	0.118 in (3 mm)

